High bay luminaire ACANEO - HIAL 30000/850/W/DALI

113374000-00692855

Waldmann
ENGINEER OF LIGHT.

fitted with	LED Energy efficiency category A+
work equipment	adjustable electronic ballast; digital DALI
connected load	220-240V; 50/60Hz
power consumption	approx. 230 W
power factor	approx. 0,950
lens	W optics; wide beam
luminous flux	approx. 30000 lm
luminous efficacy	approx. 130 lm/W
Beam Angle	90°
light colour	neutral white, approx. 5000 K
color rendering index (CRI)	> 80
consistent white light of	< 3 SDCM
glare-free	Faceted optic
unified glare rating	< 23
system of protection	IP 65
class of protection	I
technology	DALI, continuously dimmable
luminaire body	aluminium, powder-coated, white aluminium
lamp cover	acrylic clear
weight (net)	approx. 10.8 kg
mains supply	built-in plug US~ConnectionStandard
fastening	(separately available)
minimum ambient temperature	-30 °C
maximum ambient temperature	+50 °C
Overvoltage resistance	>= 4000 V
Residual light current	L80B10 after 60;000 h (according to IES LM 80 and TM 21-11)

RST 20i5 Einbau



luminous intensity





Errors and technical changes excepted. Images can vary from original.
Photometric and electrical data may vary due to component tolerances.

www.waldmann.com

© 10.2017 H. Waldmann GmbH & Co. KG